


Digital Gauge Package Copy:

- Easy to read backlit display
- Accurate readings
- Supports multiple refrigerants
- Built in Pressure/Temperature chart
- Compatible with many different manifolds

Front

Specifications

Operating Temperature	0°C ~ 50°C; 32°F ~ 122°F
Storage Temperature	-20°C ~ 70°C; -4°F ~ 158°F
Measurement Units	psi; BAR; kPa; kg/cm ² °C (Celsius); °F (Fahrenheit)
Operating Range	
Low Pressure Gauge	30~0 inHg, 0~250 psi, -1~17.5 BAR, -100~1750 kPa, -1~17.5 kg/cm ²
High Pressure Gauge	0~800 psi, -1~55.15 BAR, -100~5515 kPa, -1~56.25 kg/cm ²
Accuracy	
Low Pressure Gauge	± 1% FSO ± 1 LSD
High Pressure Gauge	± 1% FSO ± 1 LSD for 0~500 psi range ± 5% FSO ± 1 LSD for 500~800 psi range
Resolution	
Low Pressure Gauge	0.2 psi; 0.05 BAR; 1 kPa; 0.05 kg/cm ²
High Pressure Gauge	0.5 psi; 0.05 BAR; 5 kPa; 0.05 kg/cm ²
Temperature	1°C / 1°F
Display	Positive LCD 50 mm x 30 mm w/ blue backlight (backlight has 30-second auto-shutoff)
Power Requirement	Three 1.5V AAA alkaline batteries
Battery Life	140 hours
ESD	Contact at ± 4 kV; air discharge at ± 8 kV
Battery Indicator	

FSO = Full Scale Output
LSD = Least Significant Digit