




655 Eisenhower Drive
Owatonna, MN 55060-0995 USA
Phone: (507) 455-7000
Tech. Serv.: (800) 533-6127
Fax: (800) 955-8329
Order Entry: (800) 533-6127
Fax: (800) 283-8665
International Sales: (507) 455-7223
Fax: (507) 455-7063

Form No. 552750

Parts List & Operating Instructions for:

8100

© 2009 SPX
Rev. A February 10, 2009



Fluid Extractor—10 Liter

Manual Operation

1. Close the shutoff valve on top of the 8100 by fully turning the valve clockwise or counterclockwise.
2. Open the shutoff valve on the 8100-1 suction adapter hose. Turn the valve 1/4 turn so the valve handle is in-line with the hose.
3. Move the pump handle on the 8100 up and down to start extracting fluid. Once the fluid has begun to be drawn into the 8100, stop pumping. The siphon effect created will continue to draw the fluid into the 8100.

Air Pump Operation

1. Open the shutoff on the 8100-1 suction adapter hose. Turn the valve 1/4 turn so the valve handle is in-line with the hose.
2. Connect shop air to the air fitting on the 8100.
3. Open the shutoff valve on the air supply valve. Turn the valve 1/4 turn so the valve handle is in-line with the air supply line.
4. The air pump will draw fluid into the 8100.

Brake Bleeder Suction Hose

Refer to the vehicle service manual, and follow the manufacturer's brake bleeding sequence.

CAUTION: To prevent equipment damage, do not completely empty the master cylinder of brake fluid.

1. Attach the 8100-2 hose to the brake bleeder.
2. With the air pump operating, open the brake bleeder screw 1/2 to 1 turn. Brake fluid will be sucked through the 8100-2 hose and into the 8100.
3. Close the bleeder screw when no air bubbles are seen in the fluid being sucked through the 8100-2 hose.
4. Check the brake fluid level in the master cylinder, and refill if needed.
5. Repeat the procedure for the next bleeder.

To empty the 8100, remove the 8100-1 suction adapter hose and pour the contents into an appropriate waste container.



CAUTION: To prevent personal injury, wear eye protection that meets ANSI Z87.1 and OSHA standards.

Setup

1. Attach the 8100-1 hose (with the quick coupler and shutoff valve) to the fluid extractor as shown.
2. Close the shutoff valve on the hose by fully turning the valve clockwise or counterclockwise.
3. Select and insert the appropriate suction tube into the opening of the fluid to be extracted. If using the brake bleeder suction hose to bleed brakes, attach the suction tube to the brake bleeder on the wheel cylinder or caliper. *Note: The air pump operation works best for bleeding brakes.*
4. Attach the selected suction tube to the quick coupler on the 8100-1 suction adapter hose.
5. Decide whether the 8100 will be operated manually or with shop air.