




Easy Lever Wheel Dollies

Gives technicians the leverage they need to easily remove or install truck tire-and-wheel assemblies.

- Heavy-duty construction capable of toting 300 pounds.
- Onboard rollers that make stud-hole alignment a snap.
- Spring-loaded kickstand for handy parking.
- Two models that, together, can accommodate tire diameters from 24 to 48 inches.
- Rugged tubular steel construction.

No. 5096A Heavy-duty Easy Lever wheel dolly. With a width of 26", this dolly handles tire diameters of 36" to 48".

No. 5095A Easy Lever wheel dolly. With a width of 22", this dolly handles tire diameters of 24" to 36".



Back Buddy™ II

Remove, transport, service, and install heavy truck brake drums and hub assemblies.

- Fast-motion ratcheting jack with 14 inches of vertical lift.
- Pneumatic rear tires smoothly roll across any shop floor.
- Tilting mechanism to achieve the exact angle necessary for precise reassembly.
- Fold-down handle for open access to the work area.
- Onboard lube tray and toolbox.
- An array of optional adapter sets capable of grabbing almost any truck hub assembly or brake drum, inboard or outboard.

No. 5090 Back Buddy™ II.



Bottle Jacks

- Base, pressure cylinder, and oil reservoir form one internal part, which results in a stronger jack.
- Piston never contacts cylinder, so pressure will be absorbed and not damage jack if vehicle tilts.
- The No. 5213T is telescopic, allowing for very low initial height with high lifting.

No. 5213 12-Ton Bottle Jack.

No. 5221 20-Ton Bottle Jack.

No. 5213T 12-Ton Telescopic Bottle Jack.


Transfer Tanker

- Draining oil from a large displacement engine and getting it to your bulk storage container is a snap.
- Used oil is collected in a reservoir, which then rolls smoothly on 4" free-wheeling casters to your storage location.
- Pump moves five gallons a minute through the 8-foot transfer hose.
- Handle is removable for easy storage.
- Screen attached to reservoir allows assembly to be stored on its side.
- Can also be used for transferring antifreeze.

No. 5077 Low profile Transfer Tanker is only 7-1/2" from floor to top of reservoir.

No. 5097 Low profile Transfer Tanker is only 7-1/2" from floor to top of reservoir. Comes equipped with an electric pump (No. 528093), and a 15-gallon reservoir.

No. 5097 Low profile Transfer Tanker is only 7-1/2" from floor to top of reservoir. Comes equipped with a pneumatic pump (No. 529966), and a 15-gallon reservoir.



Air/Hydraulic Pump

- Ideal all-around power source develops 10,000 PSI at 100 PSI air.
- Two-stage release mechanism; internal relief valve.
- 98 cu. inches of usable oil.
- Covered by OTC Lifetime Marathon Warranty®.

No. 4020 Air/Hydraulic Pump.



Heavy-Duty Wheel Step

- Tire-mounted wheel step provides quick, easy access to underhood components.
- Fits heavy-duty vehicles (Class 7/8).
- 300-pound capacity.
- Installs in seconds; adjusts to fit 22-1/2" to 24" wheel sizes.
- Non-skid platform surface.
- Covered by OTC Lifetime Marathon Warranty®.

No. 1734A Heavy-duty Wheel Step.



Shown Folded